



## 0-421-08 - LED Flood / Warning Lamp

Durite LED Combo Flood and Warning Lamp. 10-30VDC. Raw Power: work light 36w,warning light 15W Effective Power: work light 29w,warning light 13W, Raw Lumen: Flood 5700LM, Effective Lumen: Flood 3800LM. Fly Lead 40cm Cable. Housing Material: Aluminium Alloy, Lens Material: PC, Bracket: Stainless Steel. E Marked R10, R65.

Flash Patterns: 1. Single flash (Quick) , 2.326HZ ECE R65 Pattern, 2. Single flash (Slow), 1HZ, 3. Double flash, 2.083HZ  
4. 3 flash, 1.087 HZ, 5. 4 flash, 1.408HZ, 6. 5 flash, 1.205HZ, 7. Slow single flash & Quick single flash, 1.01HZ, 8. Slow single flash & Quick double flash, 1.351HZ, 9. Slow single flash & Quick 3 flash, 1.667HZ, 10. Slow single flash & Quick 4 flash, 1.266HZ

### Fly leads

Red: Positive

Blue: Warning

Black: Negative

Yellow: Synchronization/ Switch Flash Pattern

**THE TRUSTED QUALITY BRAND FOR PROFESSIONALS**



## TECHNICAL SPECIFICATIONS

Type	LED Work Lamp with Warning Function
Voltage	10-30VDC
LED's	30 x 1.2W Work / 30 x 0.5W Warning
Power (effective)	36W (29W) Work / 15W (13W) Warning
Current Draw 12/24V	Work 2.42A / 1.21A Warn 1.08A / 0.54A
Lumens (effective)	5700Lm (3800Lm)
IP Rating	IP67, IP69K
Material Construction	Aluminium with PC Lens. Bracket SS304
Weight	0.660Kg
Dimensions	Please see below
Operating Temperature	-40°C ~ +50°C
Storage Temperature	-40°C ~ +50°C
Certificate	UKCA CE E Mark R10, R65

## TECHNICAL DRAWING

